

RAPID AIR PNEUMATSKI DODAVAČI

Model	Širina materijala	Max duljina dodavanja	Debljina materijala	Ciklusa / min	Vučna snaga
A2	1 – 1/2" (38.1mm)	2" (50mm)	.002" – .040" (.051-1.02mm)	260	20 lbs (9.1kg)
A4	1 – 1/2" (38.1mm)	4" (101mm)	.002" – .040" (.051-1.02mm)	200	20 lbs (9.1kg)
A6	1 – 1/2" (38.1mm)	6" (152mm)	.002" – .040" (.051-1.02mm)	160	20 lbs (9.1kg)
B2	2 – 1/2" (63.5mm)	2" (50mm)	.002" – .040" (.051-1.02mm)	230	20 lbs (9.1kg)
B4	2 – 1/2" (63.5mm)	4" (101mm)	.002" – .035" (.051-0.89mm)	175	20 lbs (9.1kg)
C3	3" (76.2mm)	3" (76mm)	.003" – .075" (.076-1.91mm)	195	45 lbs (20.5kg)
C6	3" (76.2mm)	6" (152mm)	.003" – .062" (.076-1.57mm)	140	45 lbs (20.5kg)
C12	3" (76.2mm)	12" (305mm)	.003" – .062" (.076-1.57mm)	85	45 lbs (20.5kg)
D3	4" (101.6mm)	3" (76mm)	.003" – .075" (.076-1.91mm)	175	45 lbs (20.5kg)
D6	4" (101.6mm)	6" (152mm)	.003" – .062" (.076-1.57mm)	135	45 lbs (20.5kg)
W6	2" (50.8mm)	6" (152mm)	.003" – .090" (.076-2.29mm)	140	100 lbs (45.5kg)
W12	2" (50.8mm)	12" (305mm)	.003" – .062" (.076-1.57mm)	85	100 lbs (45.5kg)
W20	2" (50.8mm)	20" (508mm)	.003" – .050" (.076-1.27mm)	50	100 lbs (45.5kg)
F4	6" (152mm)	4" (101mm)	.004" – .075" (.1-1.91mm)	160	100 lbs (45.5kg)
F6	6" (152mm)	6" (152mm)	.004" – .075" (.1-1.91mm)	130	100 lbs (45.5kg)
F12	6" (152mm)	12" (305mm)	.004" – .050" (.1-1.27mm)	70	100 lbs (45.5kg)
F20	6" (152mm)	20" (508mm)	.004" – .035" (.1-0.89mm)	35	100 lbs (45.5kg)
H4	8" (203mm)	4" (101mm)	.004" – .075" (.1-1.91mm)	160	100 lbs (45.5kg)
H8	8" (203mm)	8" (203mm)	.004" – .062" (.1-1.57mm)	105	100 lbs (45.5kg)
FX6	6" (152mm)	6" (152mm)	.005" – .150" (.13-3.81mm)	105	145 lbs (66kg)
FX12	6" (152mm)	12" (305mm)	.005" – .150" (.13-3.81mm)	60	145 lbs (66kg)
L6	12" (305mm)	6" (152mm)	.005" – .090" (.13-2.29mm)	105	145 lbs (66kg)

RAPID AIR PNEUMATSKI DODAVAČI

Model	Širina materijala	Max duljina dodavanja	Debljina materijala	Ciklusa / min	Vučna snaga
L12	12" (305mm)	12" (305mm)	.005" – .090" (.13-2.29mm)	60	145 lbs (66kg)
P6	16" (406mm)	6" (152mm)	.005" – .075" (.13-1.91mm)	105	145 lbs (66kg)
P12	16" (406mm)	12" (305mm)	.005" – .062" (.13-1.57mm)	60	145 lbs (66kg)
LX12	12" (305mm)	12" (305mm)	.005" – .125" (.13-3.18mm)	50	250 lbs (114kg)